


### Elite



Product ID *	L	W
VL/WGL-001-LED042xx	250	190

All Dimensions in "mm"



### Specifications & Features

- . Die cast Aluminum housing polyester powder coated with highly efficient optical grade PC cover
- . > 40% energy saving Vis a Vis Conventional HID Well glass
- . Over load, over voltage & short circuit protection
- . Integral constant current driver with PF > 95%
- . More than 85% driver efficiency with THDi < 10%
- . Equipped with 10KV Surge suppression Protection
- . Wide operating voltage 120 - 285V
- . Color Rendering Index (CRI) > 80
- . Working ambient temperature -10°C to + 50°C
- . Rated Life 50,000Hrs (Ta= 30°C @ L70)
- . High intensity of illumination with 120° view angle
- . Flicker free instant start electronic operation
- . Electric wave & radio interference free
- . Without mercury, UV & IR radiation
- . IP 65 / IP 66 Ingress Protection

### Applications

- . Power Plant
- . Cement Plant
- . Steel Plant
- . Fertilizer Industries
- . Security Lighting
- . Conveyor

### Installation & Maintenance

- . Mounting with hook, chain or Cable
- . Option for loop in loop out can be provided
- . Power Supply should be disconnected before service

Note: Earthing (⚡) must be connected properly to avoid any premature failure.

### Technical & Ordering Information

Product ID / Ordering Code	Product Description	Wattage(W)	Nominal Voltage(V)	Mains Current(A)	CCT (K)	Lumen (lm)
VL/WGL-001-LED04265	Elite LED Well glass 42/CW	42	230	0.19	6500	3350

\*xx also available in 4000K & 5000K CCTs on request.

COMPLIANT



### Intensity Distribution Diagram

Light Intensity curve for reference only

